Videopark

AHDCAMERA

INDOOR AND OUTDOOR SURVEILLANCE

1/3" 2 MP SONY IMX322 CMOS Sensor

- 3.6 mm Fix Len Bullet Camera
- Electronic Shutter 1/25s~100,000s
- Support Switch to analog output

IP66 1080

VP-HDA-BDS2200-AP
AHD 1080P Dome Camera

VP-HDA-QS2200-AP
AHD 1080P Bullet Camera

1/4" 1.2 MP CMOS Sensor

VP-HDA-QSE2120-AP
AHD Outdoor Bullet
Waterproof IR Camera

VP-HDA-BDSE2120-AP
AHD Indoor Dome Camera

- Support 25fps@720P
- 2pcs IR Array Lights.
- Max IR View Distance 30M
- High speed, long distance real-time transmission

IP66 720P

RoHS COMPLIANT FC CE

www.videopark.com.cn

Videopark

AHDCAMERA

Model	VP-HDA-QSE2120-AP	VP-HDA-BDSE2120-AP	VP-HDA-QS2200-AP	VP-HDA-BDS2200-AP
Image Sensor	1/4" 1.2MP CMOS Sensor		1/3" 2.0MP SONY IMX322 CMOS Sensor	
Image / TV System	PAL			
Effective Pixels	1280(H) × 720(V)		1920(H) × 1080(V)	
Mini. Illumination	0.01Lux@（F1.2, AGC ON）, 0 Lux with IR			
Electronic Shutter	1/25s～1/100,000s			
Video standard	AHD standard definition			
Video Frame Rate	1280×720@25 fps		1920×1080@25 fps	
LED & IR Distance	2pcs IR Array Lights,Max IR View Distance 30M			
Day & Night	ICR			
D / N Mode	-		Auto / Black / Color	
Exposure Mode	Auto/BLC			
White Balance	Auto White Balance (AWB)			
Noise Reduction / WDR	2D-DNR, DWDR			
Lens	3.6mm Fix Len			
Video Output	1-channel BNC AHD output, Support switch to analog output			
OSD / UTC	-		Support	
Transmission Distance	Over 500m via 75-3 coaxial cable		-	
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)			
Protection Grade	IP 66			
Power Supply	DC 12V±10%, 2W			
Operating Temperature	-10°C to +50°C, RH 80% Max			
Operation Humidity	-10% - 90%			
Power Supply	3W MAX			
Storage temperature	-20°C to +60°C, RH 90% Max			
Dimension	L187.34*W63.93*H64 mm	Φ98.75*H78.99 mm	L187.34*W63.93*H64 mm	Φ98.75*H78.99 mm
Weight(net)	450 g	275 g	450 g	275 g

SPECIFICATION